## IN THE CLAIMS

Please enter the amended claims given below.

wellbore;

## Claims 1-42 canceled.

1 78.

(new) A method for utilizing flowable devices in a wellbore, the method comprising:

- 3
- (a) providing at least one flowable device into a drilling tubular in the
- 4

2

- (b) providing a unique address to the at least one flowable device; and
- 6
- (c) using a drilling fluid in the drilling tubular for flowing said at least one
- \_
- flowable device to a downhole location and performing a function selected
- Ü
- from (i) providing information to a downhole controller, and, (ii)

retrieving information from a downhole device.

9

10

(new) The method of claim 78, wherein selecting the at least one flowable device comprises selecting the at least one flowable device from a group consisting of:

(i) a device having a sensor for providing a measure of a parameter of interest; (ii) a device having a memory for storing data therein; (iii) a device carrying energy that is transmittable to another device; (iv) a solid mass carrying a chemical that alters a state when said solid mass encounters a particular property in the wellbore; (v) a device carrying a biological mass; (vi) a data recording device; (vii) a device that is adapted to take a mechanical action, and (viii) a self-charging

device due to interaction with the working fluid in the wellbore.

10 45

(new) The method of claim 78, said function comprises making a measurement of a parameter of interest and wherein said selecting the at least one flowable device comprises selecting a device that provides a measurement selected from a group consisting of: (i) pressure; (ii) temperature; (iii) flow rate; (iv) vibration; (v) presence of a particular chemical in the wellbore; (vi) viscosity; (vii) water saturation; (viii) composition of a material; (ix) corrosion; (x) velocity; (xi) a physical dimension; and (xi) deposition of a particular matter in a fluid.

1 81.

(new) The method of claim 78, wherein selecting the at least one flowable device comprises selecting a flowable device that is adapted to carry data that is one of (i) prerecorded on the at least one flowable device; (ii) recorded on the at least one flowable device downhole; (iii) self recorded by the at least one flowable

014-15383USC2

	5		device; (iv) inferred by a change of a state associated with the at least one
	6		flowable device.
Wh	7 1 2	4 <sup>7</sup> , 82.	(new) The method of claim 78, wherein selecting the at least one flowable device comprises selecting a device that is one of: (i) resistant to wellbore temperatures;
	3		(ii) resistant to chemicals; (iii) resistant to pressures in wellbores; (iv) vibration
	4		resistant; (v) impact resistant; (vi) resistant to electromagnetic radiation; (vii)
	5		resistant to electrical noise; and (viii) resistant to nuclear fields.
	6 1 2	49 83.	(new) The method of claim 78 further comprising recovering said at least one flowable device.
	3 1 2 3	49 84.	(new) The method of claim 78, wherein the at least one flowable device further comprises a plurality of flowable devices, each such flowable device adapted to perform at least one task.
	1	5 <sup>0</sup> 85.	(new) The method of claim 84, further comprising providing the plurality of
	2		flowable devices in a manner that is one of: (i) timed release, (ii) time
	3		independent release, (iii) on demand release, and (iv) event initiated release.
	1 2	51 86.	(new) The method of claim 84 further comprising providing the plurality of flowable devices at time intervals such that some of said plurality of flowable
		•	are means of the control of

	3		devices remain in the wellbore at any given time, thereby forming a network of
	3		dovices remain an area and a second a second and a second a second and
	4		devices in the wellbore.
	5	52	5 <sup>1</sup> /
	1	87.	(new) The method of claim 86 wherein at least one of the plurality of devices
Pol	2		remaining in the wellbore communicates with at least one other of the plurality
m / n	3		devices remaining in the wellbore.
	4	63,	4 <sup>3</sup> ,
	1	<b>88</b> .	(new) The method of claim 78 further comprising implanting a plurality of space
	2		apart flowable devices in said wellbore during drilling of said wellbore.

3

im 78 further comprising implanting a plurality of spaced apart flowable devices in said wellbore during drilling of said wellbore.